

Monocrystalline 120 cells

MARS



Guaranteed positive output tolerance of 0 ~ +5 Wp by single measuring



3.2 mm anti-reflective glass



BLACK | BLACK




Maximum stability through aluminium soft grip frame



Maximum 5400 Pa snow load



15 years manufacturer's warranty
25 years linear performance guarantee



OUTPUT: 320 - 330 WATT

MARS monocrystalline 120 halfcut cell series is one of the top efficiency series. Dimensionally close to the conventional 60 cell modules, halfcut cells are split in two halves to improve the performance and they are arranged in two parallel strings for a better management of shading. MARS black | black edition with black backsheets and a 35 mm black anodized aluminium frame, combines visual attractiveness to conversion efficiency over 19 %.



power for a better world

Test uncertainty for Pmax: ±3 %
Voc and Isc Tolerance: ±3 %

STC	A-HCM320/120	A-HCM330/120
Maximum Power (Pmax) (W)	320	330
Open Circuit Voltage (Voc) (V)	40.42	41.02
Short Circuit Current (Isc) (A)	10.15	10.29
Voltage at Maximum Power (Vmpp) (V)	33.52	34.03
Current at Maximum Power (Impp) (A)	9.53	9.70
Module Efficiency (%)	18.89	19.48

STC (Standard Testing Condition): Irradiance 1000 W/m², Cell Temperature 25 °C, Spectra at AM 1.5

Electrical Parameters at NOCT	A-HCM320/120	A-HCM330/120
Maximum Power (Pmax) (W)	236	243
Open Circuit Voltage (Voc) (V)	37.13	37.61
Short Circuit Current (Isc) (A)	8.12	8.23
Voltage at Maximum Power (Vmpp) (V)	33.30	33.78
Current at Maximum Power (Impp) (A)	7.10	7.20

NOCT (Nominal Operating Cell Temperature): Irradiance 800 W/m², Ambient Temperature 20 °C, Spectra at AM 1.5, Wind at 1 m/s


Temperature Characteristics	
Pmax Temperature Coefficients (W / °C)	-0.35 % / °C
Voc Temperature Coefficients (V / °C)	-0.28 % / °C
Isc Temperature Coefficients (A / °C)	+0.05 % / °C
Noct Nominal Operating Cell Temperature (°C)	45 ±2 °C

Operating Conditions	
Operating Module Temperature	-40 °C ~ +85 °C
Maximum System Voltage	1500 V
Maximum Series Fuse Rating	20 A
Power Tolerance	0 ~ +5 W
Maximum Static Load Front	5400 Pa tested 8000 Pa
Maximum Static Load Back	2400 Pa
Application Class	Class A

Specifications	
Cell Type	Mono G1 158.75
Weight	19 kg ±3 %
Dimensions	1700x996x35 mm (±2 mm)
Cable Cross Section Size	4 mm ² , cable approx 110 cm, QC4 compatible
No. of cells	120 (6x20)
Junction Box	IP67, 3 diodes
Frame	Black anodized aluminium
Front glass	3.2 mm high transmission, low iron, tempered glass

Packing Details	
Container Type	40'HC
No. of Pallets	26
Pieces per Pallet	30
Total quantity of modules	780

(1700x996x35)



I-V Curve: (A-HCM330)

